

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)


PCT

(10) International Publication Number
WO 2005/052326 A1

- (51) International Patent Classification⁷: **F01L 13/00**, 1/18
- (21) International Application Number:
PCT/GB2004/004455
- (22) International Filing Date: 21 October 2004 (21.10.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
0325278.0 29 October 2003 (29.10.2003) GB
- (71) Applicant (for all designated States except US): **RI-CARDO UK LIMITED**, [GB/GB]; Bridge Works, Shoreham-by-Sea, West Sussex BN43 5FG (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KRÁTK , Martin** [CZ/CZ]; Grunzinská 3/1384, Prague 10 (CZ).
- (74) Agents: **JENNINGS, Nigel, Robin et al.**; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

[Continued on next page]

(54) Title: **ENGINE VALVEGEAR**



(57) Abstract: Valvegear for an internal combustion engine of reciprocating piston type includes a valve member (6), which cooperates with a valve seat (4) and is biased into the closed position by a spring (7). The valve member (6) includes a valve stem (8) in contact with a pivotally mounted rocker arm (10) which carries a first roller (14) in rolling contact with a first engagement surface (20) on a rocking lever (16), which is mounted to pivot about a rocking shaft (18). The rocking lever (16) has a second engagement surface (22) in rolling contact with a second roller (24) carried by an intermediate lever (26). The intermediate lever (26) carries a third roller, which may be the same as the roller (24) or a different roller, in rolling engagement with a cam (30) carried by a camshaft (32). The second engagement surface (22) is of generally arcuate section and the distance between it and the axis of the camshaft increases in one direction of the arcuate length of the second engagement surface. A gap is thus defined between the second engagement surface (22) and the cam (30) in which the third roller (24) is received. The intermediate lever (26) is connected to actuating means (29) arranged to move it selectively in a direction transversely of the width of the gap.

WO 2005/052326 A1



SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*